

Express Zone, A- Wing, Unit No. 501-505, W E Highway, Malad (E), Mumbai -400097 Tel No:-61441600 , Fax No:-
61441650

Email:- info@akashpower.com

HINDUSTAN Cooling tower induction motors suitable for 415V±10%, 50Hz±5%, combined ±10%, 3 phase supply, flange mounted (B5 construction), ambient temperature 50°C, TE, Class 'F' insulation, IP55 protection, continuous rated (S1 duty) with bare shaft & key as per IS: 325 / IEC: 60034-1.

KW	HP	Frame	Type Designation	Price	KW	HP	Frame	Type Designation	Price
4 Pole, 1500 RPM					10 Pole, 600 RPM				
0.37	0.5	71	Cooling Tower	5850	1.5	2	132S	Cooling Tower	21690
0.75	1	80	Cooling Tower	7800	2.2	3	132M	Cooling Tower	35160
1.1	1.5	90S	Cooling Tower	9750	3.7	5	160M	Cooling Tower	42000
1.5	2	90L	Cooling Tower	10280	5.5	7.5	180M	Cooling Tower	63030
6 Pole, 1000 RPM					7.5	10	180L	Cooling Tower	71140
0.75	1	90S	Cooling Tower	10890	9.3	12.5	180L	Cooling Tower	75890
1.1	1.5	90L	Cooling Tower	11450	11	15	180L	Cooling Tower	84890
1.5	2	100L	Cooling Tower	12760	15	20	200L	Cooling Tower	117580
2.2	3	112M	Cooling Tower	16870	18.5	25	225MX	Cooling Tower	157090
3.7	5	132S	Cooling Tower	23210	12 Pole, 500 RPM				
5.5	7.5	132M	Cooling Tower	28700	1.1	1.5	132S	Cooling Tower	21690
7.5	10	160M	Cooling Tower	40720	1.5	2	132M	Cooling Tower	35160
9.3	12.5	160L	Cooling Tower	49520	2.2	3	160M	Cooling Tower	42000
11	15	160L	Cooling Tower	51530	3.7	5	160L	Cooling Tower	51500
8 Pole, 750 RPM					5.5	7.5	180M	Cooling Tower	66410
1.1	1.5	100L	Cooling Tower	14520	7.5	10	180L	Cooling Tower	77460
1.5	2	112M	Cooling Tower	16300	9.3	12.5	180L	Cooling Tower	88530
2.2	3	132S	Cooling Tower	22210	11	15	200L	Cooling Tower	124220
3.7	5	132M	Cooling Tower	35190	15	20	225MX	Cooling Tower	163880
5.5	7.5	160M	Cooling Tower	42200	18.5	25	250MX	Cooling Tower	212470
7.5	10	160L	Cooling Tower	51750	22	30	280SX	Cooling Tower	262190
9.3	12.5	180M	Cooling Tower	69150	30	40	280MX	Cooling Tower	287830
11	15	180L	Cooling Tower	72850	37	50	315MX	Cooling Tower	434500
15	20	200L	Cooling Tower	104260	45	60	315MX	Cooling Tower	453080