

Express Zone, A- Wing, Unit No. 501-505, W E Highway, Malad (E), Mumbai -400097 Tel No:-
61441600 , Fax No:- 61441650 Email:- info@aakashpower.com

(WEF: 15th December 2018)

HINDUSTAN Two Speed induction motors suitable for 415V±10%, 50Hz±5%, combined ±10%, 3 phase supply, foot mounted (B3 construction), ambient temperature 50°C, TEFC, Class 'F' insulation, IP55 protection, continuous rated (S1 duty) with bare shaft & key as per IS: 325 / IEC: 60034-1.

KW	HP	Frame	Polarity	Type Designation	Price
0.09/0.12	0.125/0.16	63	4/2.	2 - Speed	6050
0.25/0.25	0.33/0.33	71	4/2.	2 - Speed	6220
0.30/0.40	0.4/0.54	71	4/2.	2 - Speed	7500
0.37/0.55	0.50/0.75	80	4/2.	2 - Speed	7970
0.45/0.60	0.60/0.80	80	4/2.	2 - Speed	9380
0.75/1.1	1.0/1.5	90S	4/2.	2 - Speed	10230
1.05/1.65	1.4/2.2	90L	4/2.	2 - Speed	12750
1.5/1.5	2.0/2.0	100L	4/2.	2 - Speed	15990
1.65/2.2	2.2/3.0	100L	4/2.	2 - Speed	16620
2.2/2.2	3.0/3.0	112M	4/2.	2 - Speed	21720
3.0/4.1	4.0/5.5	112M	4/2.	2 - Speed	22770
3.7/3.7	5.0/5.0	132S	4/2.	2 - Speed	24980
4.0/5.1	5.4/6.8	132S	4/2.	2 - Speed	26230
5.5/5.5	7.5/7.5	132M	4/2.	2 - Speed	36150
6.0/7.5	8.0/10.0	132M	4/2.	2 - Speed	37980
7.5/7.5	10.0/10.0	160M	4/2.	2 - Speed	41250
9.0/10.5	12.0/14.0	160M	4/2.	2 - Speed	53160
11.0/11.0	15.0/15.0	160L	4/2.	2 - Speed	62570
12.0/14.2	16.0/19.0	160L	4/2.	2 - Speed	65680
15.0/15.0	20.0/20.0	180M	4/2.	2 - Speed	68130
18.0/21.0	24.0/28.0	180L	4/2.	2 - Speed	74690
22.0/24.0	30.0/32.0	200L	4/2.	2 - Speed	102940
30.0/36.0	40.0/48.0	225MX	4/2.	2 - Speed	158850
41.0/52.0	55.0/70.0	250MX	4/2.	2 - Speed	210460
60.0/75.0	80.0/100.0	280SX	4/2.	2 - Speed	296370
70.0/85.0	94.0/114.0	280MX	4/2.	2 - Speed	343590
85.0/100.0	114.0/134.0	315SX	4/2.	2 - Speed	486120
100.0/120.0	134.0/160.0	315MX	4/2.	2 - Speed	572240
0.093/0.12	0.125/0.16	80	8/4.	2 - Speed	8900

KW	HP	Frame	Polarity	Type Designation	Price
0.18/0.25	0.25/0.33	80	8/4.	2 - Speed	9520
0.25/0.37	0.33/0.50	90S	8/4.	2 - Speed	9940
0.37/0.55	0.50/0.75	90L	8/4.	2 - Speed	11180
0.55/0.93	0.75/1.25	100L	8/4.	2 - Speed	12870
0.75/1.1	1.0/1.5	100L	8/4.	2 - Speed	14780
1.1/1.8	1.5/2.4	112M	8/4.	2 - Speed	16700
1.8/2.7	2.4/3.6	132S	8/4.	2 - Speed	22480
2.2/3.7	3.0/5.0	132M	8/4.	2 - Speed	36450
3.0/3.9	4.0/5.2	132M	8/4.	2 - Speed	38260
3.7/5.5	5.0/7.5	160M	8/4.	2 - Speed	41710
5.5/9.3	7.5/12.5	160L	8/4.	2 - Speed	51160
7.5/10.5	10.0/14.0	180M	8/4.	2 - Speed	68390
9.3/12.0	12.5/16.0	180L	8/4.	2 - Speed	72130
11.0/15.0	15.0/20.0	200L	8/4.	2 - Speed	103120
15.0/22.0	20.0/30.0	200L	8/4.	2 - Speed	116000
18.5/24.0	25.0/32.0	225MX	8/4.	2 - Speed	155720
26.0/34.0	35.0/45.0	250MX	8/4.	2 - Speed	201780
30.0/37.0	40.0/50.0	250MX	8/4.	2 - Speed	225830
37.0/45.0	50.0/60.0	280SX	8/4.	2 - Speed	283910
28.0/55.0	37.0/75.0	280MX	8/4.	2 - Speed	311630
45.0/55.0	60.0/75.0	315SX	8/4.	2 - Speed	377070
55.0/75.0	75.0/100.0	315MX	8/4.	2 - Speed	470450
0.12/0.15	0.16/0.20	71	6/4.	2 - Speed	7960
0.30/0.45	0.40/0.60	80	6/4.	2 - Speed	8980
0.45/0.67	0.60/0.90	90S	6/4.	2 - Speed	9800
0.75/1.1	1.0/1.5	90L	6/4.	2 - Speed	10520
1.05/1.5	1.4/2.0	100L	6/4.	2 - Speed	12950
1.65/2.2	2.2/3.0	112M	6/4.	2 - Speed	16160
2.7/3.9	3.6/5.2	132S	6/4.	2 - Speed	23450
4.2/5.7	5.6/7.6	132M	6/4.	2 - Speed	27490
5.5/9.0	7.5/12.0	160M	6/4.	2 - Speed	40300
9.0/12.0	12.0/16.0	160L	6/4.	2 - Speed	50930
11.0/16.5	15.0/22.0	180L	6/4.	2 - Speed	70060
16.5/22.0	22.0/30.0	200L	6/4.	2 - Speed	99470
22.0/30.0	30.0/40.0	225MX	6/4.	2 - Speed	152060
30.0/37.0	40.0/50.0	250MX	6/4.	2 - Speed	203740
30.0/45.0	40.0/60.0	280SX	6/4.	2 - Speed	255080
45.0/55.0	60.0/75.0	280MX	6/4.	2 - Speed	291280
3.7/5.5	5.0/7.5	160M	8/6.	2 - Speed	44630

KW	HP	Frame	Polarity	Type Designation	Price
5.5/7.5	7.5/10.0	160L	8/6.	2 - Speed	54720
6.3/9.3	8.5/12.5	180M	8/6.	2 - Speed	73130
7.5/11.0	10.0/15.0	180L	8/6.	2 - Speed	77090
11.0/15.0	15.0/20.0	200L	8/6.	2 - Speed	110280
16.8/22.0	22.5/30.0	225MX	8/6.	2 - Speed	166540
22.0/30.0	30.0/40.0	250MX	8/6.	2 - Speed	215860