

ALUMINIUM WIRES & CABLES

"POLYCAB" SINGLE CORE PVC INSULATED 1100 VOLTS SOLID ALUMINIUM CONDUCTOR WIRES AS PER IS 694		"POLYCAB" SINGLE CORE PVC INSULATED 1100 VOLTS STRANDED ALUMINIUM CONDUCTOR WIRES AS PER IS 694		"POLYCAB" PVC INSULATED AND SHEATHED TWIN CORE & THREE CORE FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE STRANDED ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694		
SQ.MM	RATE/ 100M	SQ.MM	RATE/ 100M	NO.OF CORES	SQ.MM	RATE/ 100M
1.5	435	1.5	445			
2.5	670	2.5	680	2	1.5	1610
4	880	4	920	2	2.5	2280
6	1340	6	1380	2	4	3220
10	1990	10	2070	2	6	4210
"POLYCAB" SINGLE CORE PVC INSULATED & SHEATHED 1100 VOLTS STRANDED ALUMINIUM CONDUCTOR WIRES AS PER IS 694		16	2980	2	10	6530
		25	4635	2	16	8650
		35	6250	2	25	12300
		50	8400	2	35	15700
SQ.MM	RATE/ 100M	70	11200	2	50	19900
1.5	660	95	13100	3	1.5	2200
2.5	815	120	19000	3	2.5	3300
4	1550	150	23600	3	4	4500
6	2110	185	29300	3	6	6400
10	2890	240	38100	3	10	9300
16	4110	300	47500	3	16	12700
25	5985	400	61000	3	25	17700
35	7630	500	77600	3	35	23100
50	10100	630	98300	3	50	29300
"POLYCAB" PVC INSULATED AND SHEATHED TWIN CORE & THREE CORE FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE SOLID ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694				"POLYCAB" XLPE INSULATED AND PVC SHEATHED CABLE WITH EACH CORE HAVING STRANDED ALUMINIUM CONDUCTOR SERVICE CABLES GENERALLY CONFORMING TO IS 694		
NO.OF CORES	SQ.MM	RATE/100M	NO.OF CORES	SQ.MM	RATE/ 100M	
2	1.5	1495	2	4	2980	
2	2.5	2185	2	6	4230	
2	4	2980	2	10	5255	
2	6	4135	2	16	7655	
2	10	6350				
3	1.5	2070				
3	2.5	3220				
3	4	4665				
3	6	5900				
3	10	9060				
Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97. Tel: 022 6144 1600; Email: info@akashpower.com; www.akashpower.com				01.01.2020		