

( WEF 01st January 2020 )

## Building Management System Cable (BMS)

Flexible Bare Copper Conductor, PVC Insulated, Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Rate/100m)

Cores	0.5 sq mm (16/.2)	0.75 sq mm (24/.2)	1.0 sq mm (32/.2)	1.5 sq mm (30/.25)	2.5 sq mm (50/.25)
2	4500	5600	6300	8200	12400
3	5600	7100	8400	10800	16800
4	5700	8800	10200	15500	24200
5	8000	12300	12400	17200	26300
6	9000	13800	14800	19800	31200
7	9800	14100	16300	22200	35400
8	11400	15700	18400	25000	40000
10	13300	17900	22700	31000	50400
12	15700	21000	26800	37000	58900
14	18100	24400	30700	41900	68200
16	20800	27700	34800	48500	77800
19	23700	32000	40200	56200	89500
24	28300	39200	50600	70900	115900

Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97.

Tel: 022 6144 1600; Email: info@akashpower.com; www.akashpower.com

Rev.001 - 01.01.2020