



LT Cables Pricelist



WEF 12th February 2020

Polycab PVC Insulated Single Core Unsheathed Industrial (Multistrand)Cable- Flame Retardant Lead Free (FRLF)Conforming to IS-694:1990 with Bright annealed Electrolytic bare Copper Conductor for Voltage Grade 1100 Volts

Polycab PVC Insulated Single Core Unsheathed Industrial (Multistrand)Cable- Heat Resistant Flame retarded Low smoke Hologen - Lead Free Conforming to IS-694:2010 with Bright annealed Electrolytic bare Copper Conductor for Voltage Grade 1100 Volts

Size (sq.mm)	FRLF						HR	
							FRLSH-LEAD FREE (GREEN Wire)	
	45 Mtr	Coils Per Box	90 Mtrs	Coils Per Box	180 Mtrs (Box Packing)	Coils Per Box	90 Mtrs	Coils Per Box
0.75	395	48	785	28			825	28
1	515	36	1025	24	2050	12	1075	24
1.5	770	30	1535	16	3070	10	1610	16
2.5	1235	20	2465	12	4930	6	2590	12
4	1840	16	3680	8	7360	4	3865	8
6	2755	8	5510	6	11020	3	5785	6
10			9740	1				
16			15600	1				

Polycab PVC Insulated Single Core Unsheathed Industrial (Multistrand)Cable- Flame Retardant Lead Free (FRLF)/ Flame Retardant Low smoke (FRLSH) Conforming to IS-694:2010 with Bright annealed Electrolytic bare Copper Conductor for Voltage Grade 1100 Volts

Polycab PVC Insulated Single Core Unsheathed Industrial (Multistrand)Cable- Flame Retardant Zero Halogen (FRZH) /Low smoke Zero Halogen (LSZH) /Halogen Free Flame Retardant (HFFR) with Bright annealed Electrolytic bare Copper Conductor for Voltage Grade 1100 Volts

Polycab PVC Insulated Single Core Unsheathed Industrial (Multistrand)Cable- Heat Resistant Flame retarded Low smoke Hologen - Lead Free Conforming to IS-694:2010 with Bright annealed Electrolytic bare Copper Conductor for Voltage Grade 1100 Volts

Size (sq.mm)	FRLF		FRLS-H		FRZH/LSZH/HFFR		HR	
							FRLSH-LEAD FREE (GREEN Wire)	
	300 Mtr (0.75-2.5) 200 Mtr (4-16)	Coils Per Box	300 Mtr (0.75-2.5) 200 Mtr (4-16)	Coils Per Box	300 Mtr (0.75-2.5) 200 Mtr (4-16)	Coils Per Box	180 Mtrs (Pouch Packing)	Coils Per Box
0.75	2615	10	2745	10	2810	10	2150	12
1	3415	8	3585	8	3670	8	3220	10
1.5	5115	6	5370	6	5500	6	5180	6
2.5	8215	4	8625	4	8830	4	7730	4
4	8180	4	8590	4	8795	4	11570	3
6	12245	3	12860	3	13160	3		
10	21650	1	22730	1	23270	1		
16	34670	1	36400	1	37270	1		

Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97. Tel: 022 6144 1600; Email: info@aakashpower.com; www.aakashpower.com

Rev.001 - 12.02.2020