

(WEF 1st March 2019)

INDUSTRIAL JELLY FLOODED COAXIAL CABLES				LAN (COMPUTER) CABLES						
"POLYCAB" Gas Injected Physical Polyethylene Foam Insulation with Laminated Aluminium Tape and Aluminium Wire Braid, Jelly Flooded PVC Black Jacketed Industrial Coaxial Cables.				"POLYCAB" 4 Pair Unshielded Twisted Pair (UTP) LAN (Computer) Cables			"POLYCAB" 4 Pair Shielded Twisted Pair (STP) LAN (Computer) Cables			
Size	100m Unarmoured	305m Unarmoured	1000m Flexible Armoured		Unarmoured Rate per 305 m	Flexible Armoured-Rate per 1000 m	STP-Rate per 305m	Flexible Armoured-Rate per 1000m		
RG - 59	1800	5495	78500	CAT 5E	8165	87000	10100	99000		
RG - 6	2280	6955	85500	CAT 6	8920	98000	11350	108000		
RG - 11	5000	15245	121000	CCTV CABLES Rate/90m						
RG-6 CCS	1625	4965	75000	CCTV Cables 4+1			CCTV Cables 3+1			
RG-11 CCS	3345	10200	111000	3680			3245			
INDUSTRIAL TELEPHONE (SWITCHBOARD) CABLES				IND. 3C FLAT SUBMERSIBLE CABLES						
"POLYCAB" High Conductivity Solid Annealed Bare Copper industrial Telephone (Switchboard) Cables with High Density Polyethylene Insulation, Paired, Polyester and Sheathed with High Oxygen Index, Fire Retardant, PVC Compound, Grey Outer Sheath generally conforming ITD Specification				"POLYCAB" PVC Insulated and PVC Sheathed Industrial 3 Core Flat Submersible Cable with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade 1100 Volts as per IS:694/2010			"POLYCAB" Special PVC Insulated & PVC Sheathed Industrial 3 Core Flat Submersible Cables with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade 1100 Volts generally conforming to IS 694/2010.			
No. of Pairs & Size	Rate / 100m (Rs.)		Rate / 90m (Rs.)		Master Packing	Nominal Area of Conductor (sq mm)	Rate per 100m (Rs)	Nominal Area of Conductor (sq mm)	Rate per 100m (Rs)	
	0.4 mm	0.5 mm	0.4 mm	0.5 mm						
1 Pair	630	765	565	690	20	1.5	5950	6	24800	
2 Pair	1075	1320	970	1190	20	2.5	9600	10	42400	
3 Pair	1445	1955	1300	1760	16	4	14000	16	69900	
4 Pair	1775	2555	1600	2300	12			25	111600	
5 Pair	2225	3195	2005	2875	8			35	156500	
10 Pair		6100		5490	1			50	224100	
20 Pair		12100		10890	1			70	312100	
50 Pair		34000			1			95	402900	
100 Pair		65300			1			120	515000	
								150	641700	
ARMOURED TELEPHONE CABLES										
					Notes:					
No. of Pairs	Rate / 100m (0.5mm)	Master Packing		1) The above cables are supplied in 500/1000m drums.						
2 Pair	6650	Drums/Coils as required		2) Polycab Three Core Flat Submersible Cables Insulated & Sheathed with XLPE can be supplied at the same rates as given above.						
5 Pair	10500	Drums/Coils as required								
10 Pair	15300	Drums/Coils as required								
20 Pair	19500	Drums/Coils as required								
50 Pair	45900	Drums/Coils as required								
100 Pair	90800	Drums/Coils as required								
INDUSTRIAL SPEAKER WIRES										
Speaker Wires (Oxygen Free)										
Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.			
23 / 36	1735	23 / 38	1225	0.5 Sq.mm	1670	1.5 Sq.mm	4385			
40 / 36	2730	40 / 38	2040	0.75 Sq.mm	2395	2 Sq.mm	6135			
70 / 36	4775	70 / 38	3205	1 Sq.mm	3025	2.5 Sq.mm	7165			
JELLY FILLED TELEPHONE CABLES										
"POLYCAB" Jelly Filled Telephone Cables, Solid Annealed Copper, Polythene Insulated, Petroleum Jelly Filled With Poly-Al Laminare Moisture Barrier, Polythene Sheathed, Unarmoured Polythene Jacketed Telephone Cables As Per Dot/ Polycab Specification										
Size	5 Pair	10 Pair	20 Pair	50 Pair	100 Pair	200 Pair				
0.5	61	103	180	407	773	1514				
"POLYCAB" Jelly Filled Telephone Cables, Solid Annealed Copper, Polythene Insulated, Petroleum Jelly Filled With Poly-Al Laminare Moisture Barrier, Polythene Sheathed, Armoured Polythene Jacketed Telephone Cables As Per Dot/ Polycab Specification										
Size	5 Pair	10 Pair	20 Pair	50 Pair	100 Pair	200 Pair				
0.5	110	162	248	503	895	1681				