

HINDUSTAN Flameproof Standard induction motors suitable for 415V±10%, 50Hz±5%, combined ±10%, 3 phase supply, foot mounted (B3 construction), ambient temperature 50°C, TEFC, Class 'F' insulation, IP55 protection, continuous rated (S1 duty) with bare shaft & key as per IEC: 60034-1 & suitable for gas group IIB as per IS/IEC:60079-1.

KW	HP	Frame	Type Designation	Price	KW	HP	Frame	Type Designation	Price
2 Pole, 3000 RPM					4 Pole, 1500 RPM				
0.18	0.25	63FLP	Flame Proof STD	11460	0.12	0.16	63FLP	Flame Proof STD	11200
0.25	0.33	63FLP	Flame Proof STD	11540	0.18	0.25	63FLP	Flame Proof STD	11310
0.37	0.5	71 FLP	Flame Proof STD	11770	0.25	0.33	71FLP	Flame Proof STD	11500
0.55	0.75	71 FLP	Flame Proof STD	13160	0.37	0.5	71 FLP	Flame Proof STD	11560
0.75	1	80 FLP	Flame Proof STD	13550	0.55	0.75	80 FLP	Flame Proof STD	12770
1.1	1.5	80 FLP	Flame Proof STD	15160	0.75	1	80 FLP	Flame Proof STD	13260
1.5	2	90 FLP	Flame Proof STD	15900	1.1	1.5	90 FLP	Flame Proof STD	15160
2.2	3	90 FLP	Flame Proof STD	21230	1.5	2	90 FLP	Flame Proof STD	16450
3.7	5	100L FLP	Flame Proof STD	26900	2.2	3	100L FLP	Flame Proof STD	20920
5.5	7.5	132M FLP	Flame Proof STD	38190	3	4	112M FLP	Flame Proof STD	23110
7.5	10	132M FLP	Flame Proof STD	42110	3.7	5	112M FLP	Flame Proof STD	26420
9.3	12.5	160L FLP	Flame Proof STD	61230	5.5	7.5	132M FLP	Flame Proof STD	36460
11	15	160L FLP	Flame Proof STD	73920	7.5	10	132M FLP	Flame Proof STD	41510
15	20	160L FLP	Flame Proof STD	89700	9.3	12.5	160L FLP	Flame Proof STD	63510
18.5	25	160L FLP	Flame Proof STD	102040	11	15	160L FLP	Flame Proof STD	67100
22	30	180L FLP	Flame Proof STD	120540	15	20	160L FLP	Flame Proof STD	81750
30	40	200L FLP	Flame Proof STD	162680	18.5	25	180L FLP	Flame Proof STD	92440
37	50	200L FLP	Flame Proof STD	211080	22	30	180L FLP	Flame Proof STD	109870
45	60	225M FLP	Flame Proof STD	266770	30	40	200L FLP	Flame Proof STD	148020
55	75	250M FLP	Flame Proof STD	327490	37	50	225SX FLP	Flame Proof STD	192800
75	100	280S FLP	Flame Proof STD	403330	45	60	225MX FLP	Flame Proof STD	242720
90	120	280M FLP	Flame Proof STD	436150	55	75	250MX FLP	Flame Proof STD	298170
110	150	315S FLP	Flame Proof STD	505330	75	100	280SX FLP	Flame Proof STD	366120
132	180	315M FLP	Flame Proof STD	599150	90	120	280MX FLP	Flame Proof STD	373230
150	200	315M FLP	Flame Proof STD	652000	110	150	315SX FLP	Flame Proof STD	445580
160	215	315L FLP	Flame Proof STD	679280	132	180	315MX FLP	Flame Proof STD	539280
180	240	315L FLP	Flame Proof STD	814400	150	200	315MX FLP	Flame Proof STD	558320
200	270	315L FLP	Flame Proof STD	981190	160	215	315LX FLP	Flame Proof STD	566290
					180	240	315LX FLP	Flame Proof STD	677840
					200	270	315LX FLP	Flame Proof STD	783650

Express Zone, A- Wing, Unit No. 501-505, W E Highway, Malad (E), Mumbai -400097 Tel No:- 61441600 ,
Fax No:- 61441650 Email:- info@akashpower.com
(WEF: 15th December 2018)

HINDUSTAN Flameproof Standard induction motors suitable for 415V±10%, 50Hz±5%, combined ±10%, 3 phase supply, foot mounted (B3 construction), ambient temperature 50°C, TEFC, Class 'F' insulation, IP55 protection, continuous rated (S1 duty) with bare shaft & key as per IEC: 60034-1 & suitable for gas group IIB as per IS/IEC:60079-1.

KW	HP	Frame	Type Designation	Price	KW	HP	Frame	Type Designation	Price
6 Pole, 1000 RPM					8 Pole, 750 RPM				
0.18	0.25	71 FLP	Flame Proof STD	12710	0.12	0.16	71 FLP	Flame Proof STD	14770
0.25	0.33	71 FLP	Flame Proof STD	13080	0.18	0.25	80 FLP	Flame Proof STD	15080
0.37	0.5	80 FLP	Flame Proof STD	13450	0.25	0.33	80 FLP	Flame Proof STD	15240
0.55	0.75	80 FLP	Flame Proof STD	13760	0.37	0.5	90 FLP	Flame Proof STD	15740
0.75	1	90 FLP	Flame Proof STD	16030	0.55	0.75	90 FLP	Flame Proof STD	17040
1.1	1.5	90 FLP	Flame Proof STD	16550	0.75	1	100L FLP	Flame Proof STD	20610
1.5	2	100L FLP	Flame Proof STD	23900	1.1	1.5	100L FLP	Flame Proof STD	24000
2.2	3	112M FLP	Flame Proof STD	27770	1.5	2	112M FLP	Flame Proof STD	28780
3.7	5	132M FLP	Flame Proof STD	36850	2.2	3	132M FLP	Flame Proof STD	38040
5.5	7.5	132M FLP	Flame Proof STD	44610	3.7	5	132M FLP	Flame Proof STD	61530
7.5	10	160L FLP	Flame Proof STD	69020	5.5	7.5	160L FLP	Flame Proof STD	70630
9.3	12.5	160L FLP	Flame Proof STD	80440	7.5	10	160L FLP	Flame Proof STD	86160
11	15	160L FLP	Flame Proof STD	84520	9.3	12.5	180L FLP	Flame Proof STD	109520
15	20	180L FLP	Flame Proof STD	112940	11	15	180L FLP	Flame Proof STD	115340
18.5	25	200L FLP	Flame Proof STD	140420	15	20	200L FLP	Flame Proof STD	155920
22	30	200L FLP	Flame Proof STD	152330	18.5	25	225SX FLP	Flame Proof STD	193580
30	40	225MX FLP	Flame Proof STD	249750	22	30	225MX FLP	Flame Proof STD	254770
37	50	250MX FLP	Flame Proof STD	306690	30	40	250MX FLP	Flame Proof STD	312890
45	60	280SX FLP	Flame Proof STD	357850	37	50	280SX FLP	Flame Proof STD	401530
55	75	280MX FLP	Flame Proof STD	385980	45	60	280MX FLP	Flame Proof STD	410060
75	100	315SX FLP	Flame Proof STD	452610	55	75	315SX FLP	Flame Proof STD	499630
90	120	315MX FLP	Flame Proof STD	530730	75	100	315MX FLP	Flame Proof STD	585190
110	150	315MX FLP	Flame Proof STD	581880	90	120	315LX FLP	Flame Proof STD	640510
132	180	315LX FLP	Flame Proof STD	705320	110	150	315LX FLP	Flame Proof STD	714250
150	200	315LX FLP	Flame Proof STD	736150					