

(w.e.f. 3rd May 2021)

INDUSTRIAL JELLY FLOODED COAXIAL CABLES

"POLYCAB" Gas Injected Physical Polyethylene Foam Insulation with Laminated Aluminium Tape and Aluminium Wire Braid, Jelly Flooded PVC Black Jacketed Industrial Coaxial Cables.

Size	100m Unarmoured	305m Unarmoured	1000m Flexible Armoured
	1 Core	2 Core	3 Core
RG - 59	2665	8130	
RG - 6	2880	8785	79500
RG - 11	5500	16775	140500
RG-6 CCS	1610	4910	
RG-11 CCS	3300	10065	

POLYCAB IND. 3C FLAT SUBMERSIBLE CABLE

Polycab PVC / Xlpe Insulated and PVC Sheathed Industrial 3 Core Flat Submersible Cable with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade 1100 Volts as per IS:694/2010

Size in Sq. mm.	PVC Insulated Rate per 100mtr Drum Packing - 500/1000 mtrs.)	XLPE Insulated Rate per 100mtr (Drum Packing - 500/1000 mtrs.)	PVC Insulated Rate per 100mtr. (Corrogated Box Packing)
1.5	9330	9800	9120
2.5	15800	16600	15500
4	23400	24600	23000
6	33600	35300	33000
10	60000	63000	
16	95900	100700	
25	155500	163300	
35	212800	223400	

CCTV Cable

Items	UOM	Rate in Rs.
CCTV 3+1	90 MTRS	4545
CCTV 4+1	90 MTRS	5095
CCTV 3+1	180 MTRS	9090
CCTV 4+1	180 MTRS	10190
CCTV 4+1 Armoured	1000 MTRS	141000

MANUFACTURERS AUTHORISED CHANNEL PARTNER / MARKETING REPRESENTATIVE:



Cables Motors
LV Switchgears
Cable Lugs & Glands
LED Lighting & Luminaires
Transformers

Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97.
Tel: 022 6144 1600;
Email: info@aakashpower.com;
www.aakashpower.com

(w.e.f. 3rd May 2021)

LAN Cable

Item	UOM	Rate in Rs.
CAT 5e UTP PVC	305 MTRS.	11685
CAT 5e UTP FR -PVC	305 MTRS.	11685
CAT 5e UTP LSZH	305 MTRS.	12270
CAT 6 UTP PVC (Without Separator)	305 MTRS.	12475
CAT 6 UTP PVC-FR (Without Separator)	305 MTRS.	12475
CAT 6 UTP LSZH (Without Separator)	305 MTRS.	13280
CAT 6 UTP PVC (With Separator)	305 MTRS.	12665
CAT 6 UTP PVC-FR (With Separator)	305 MTRS.	12665
CAT 6 UTP LSZH (With Separator)	305 MTRS.	13570
CAT 6 FTP FR PVC	305 MTRS.	15295
CAT 6A UTP PVC	305 MTRS.	15335
CAT 6A UTP PVC-FR	305 MTRS.	15335
CAT 6A UTP LSZH	305 MTRS.	16215
CAT 6 UTP DJ (PVC-PE)	305 MTRS.	15340
CAT 6 UTP DJ (PVC-PE) with Anti Rodent	305 MTRS.	15340
CAT 6 UTP DJ (PVC-LSZH)	305 MTRS.	15250
CAT6 SFTP FR PVC	305 MTRS.	27840
CAT6 SFTP LSZH	305 MTRS.	28430
CAT6 SFTP LSZH wire Armored	305 MTRS.	49110
CAT6A FTP FR PVC	305 MTRS.	17025
CAT6A FTP LSZH	305 MTRS.	17795
CAT6 UTP- 23 AWG, ECSS FR, ARM PE with Separator	1000 MTRS.	80420
CAT6 UTP- Armoured / Flexible Armoured	1000 MTRS.	105000
CAT6 STP- Armoured / Flexible Armoured	1000 MTRS.	117500

MANUFACTURERS AUTHORISED CHANNEL PARTNER / MARKETING REPRESENTATIVE:



**Cables
Motors
LV Switchgears
Cable Lugs & Glands
LED Lighting & Luminaires
Transformers**

Add: 501-505, A-Wing, Express
Zone, W.E.H, Malad-(E), Mum- 97.
Tel: 022 6144 1600;
Email: info@akashpower.com;
www.akashpower.com

(w.e.f. 3rd May 2021)

SINGLE CORE FLEXIBLE CABLES

MULTI CORE FLEXIBLE CABLES

"POLYCAB" FR Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

"POLYCAB" PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade 1100 Volts as per IS: 694:2010

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Rate/100m)		2 Core	3 Core	4 Core	2-4 Core Packing	5 Core	6 Core
			Single Core	Packing						
0.5	16/.2	5	1030	24	3090	4040	5070	5	7015	7450
0.75	24/.2	8	1490	24	4140	5490	6910	5	9870	10500
1	32/.2	13	1955	20	5070	6830	8735	5	12700	13100
1.5	30/.25	17	2835	16	6815	9500	12400	5	17800	18600
2.5	50/.25	24	4560	12	10800	15000	19700	4	28200	29700
4	56/.3	30	7015	8	16300	22900	30000		41900	45400
6	84/.3	38	10500	6	23800	33700	44100		61900	72700
10	80/.4	52	18200	1	41900	57600	75000		107100	127100
16	126/.4	70	28300	1	69400	91000	118100		172100	
25	196/.4	88	44300	1	107700	143500	189600		270200	
35	276/.4	110	61700	1	149300	201000	264500		373800	
50	396/.4	145	87500	1	223800	288600	376800		542900	
70	354/.5	215	127100	1	297000	405600	535100		749500	
95	484/.5	260	168200	1						
120	608/.5	305	215800	1						
150	750/.5	355	267300	1						
185	925/.5	415	330100	1						
240	1210/.5	500	434000	1						
300	1527/.5	585	554300	1						
400	2036/.5	695	739200	1						
500			946000	1						
630			1192800	1						
FR Insulation :		5%								
FRLSH / HR Insulation :		10%								
HFFR :		25%								

"POLYCAB" PVC Insulated, PVC Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil							
			7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	8660	10200	12300	14400	16900	19100	22200	30100
0.75	24/.2	8	12000	14100	17400	20600	23800	27200	31800	42700
1	32/.2	13	15100	17800	22000	26100	30200	34500	40800	55600
1.5	30/.25	17	21600	25700	30600	36300	42500	48300	57000	76300
2.5	50/.25	24	34400	41100	49000	58700	68300	77800	91200	124300
4	56/.3	30	52400	62400						
6	84/.03	37								

"POLYCAB" Multi Strand Bare Copper conductor XLPE insulated PVC Sheathed Cables

Nominal Area	No/Dia of Strands	Current rating in Air at 40°C	Cu Conductor Unarmoured Cables	Cu Conductor Aluminium Armoured Cables
mm ²	No/mm		Rs (Rate / 100M)	Rs (Rate / 100M)
6	84/0.3	55	14700	20200
10	80/0.4	75	24700	34200
16	126/0.4	103	36400	42600
25	196/0.4	126	58100	65300
35	276/0.4	152	79300	87800
50	396/0.4	189	110500	122000
70	354/0.5	240	152100	167700
95	484/0.5	297	206500	215500
120	608/0.5	346	261000	272500
150	750/0.5	390	326100	340700
185	925/0.5	460	397800	410600
240	1210/0.5	552	517100	541200
300	1527/0.5	640	644500	680900
400	2036/0.5	753	859800	902400

MANUFACTURERS AUTHORISED CHANNEL PARTNER / MARKETING REPRESENTATIVE:



Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97.
Tel: 022 6144 1600;
Email: info@aakashpower.com;
www.aakashpower.com

(w.e.f. 3rd May 2021)

"POLYCAB" FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

"POLYCAB" PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade 1100 Volts as per IS: 694:2010

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Single Core (Rate/100m)	Packing	(Rate/100m)					
					1 Core	2 Core	2 Core	3 Core	4 Core	2-4 Cores
0.5	16/.2	5	1065	24	3325	4345	5450	5	7540	8000
0.75	24/.2	8	1540	24	4450	5900	7430	5	10600	11300
1	32/.2	13	2025	20	5450	7345	9400	5	13700	14100
1.5	30/.25	17	2935	16	7150	10000	13000	5	18700	19500
2.5	50/.25	24	4720	12	11300	15800	20700	4	29600	31200
4	56/.3	30	7260	8	17100	24000	31500		44000	47700
6	84/.3	38	10900	6	25000	35400	46300		65000	76300
10	80/.4	52	18800	1	44000	60500	78800		112500	133500
16	126/.4	70	29300	1	72900	95600	124000		180700	
25	196/.4	88	45900	1	113100	150700	199100		283700	
35	276/.4	110	63900	1	156800	211100	277700		392500	
50	396/.4	145	90600	1	235000	303000	395600		570000	
70	354/.5	215	131500	1	311900	425900	561900		787000	
95	484/.5	260	174100	1		562100	743400			
120	608/.5	305	223400	1		751300	970700			
150	750/.5	355	276700	1		984800	1298800			
185	925/.5	415	341700	1		1185000	1571300			
240	1210/.5	500	449200	1		1562500	2068000			
300	1527/.5	585	573700	1		1943500	2461800			
400	2036/.5	695	765100	1		2591300	3250000			
500			979100	1						
630			1234500	1						

Polycab PVC Insulated, FRLS Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal Area of Conductor (sq mm)	Number/Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil				Rate Per 100 Mtrs. Coil			
			7 Core	8 Core	10 Core	12 Core	14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	9300	11000	13200	15500	18200	20500	23900	32400
0.75	24/.2	8	12900	15200	18700	22100	25600	29200	34200	45900
1	32/.2	13	16200	19100	23700	28100	32500	37100	43900	59800
1.5	30/.25	17	22700	27000	32100	38100	44600	50700	59900	80100
2.5	50/.25	24	36100	43200	51500	61600	71700	81700	95800	130500
4	56/.3	30	55000	65500						
6	84/0.3	37								

MANUFACTURERS AUTHORISED CHANNEL PARTNER / MARKETING REPRESENTATIVE:



**Cables
Motors
LV Switchgears
Cable Lugs & Glands
LED Lighting & Luminaires
Transformers**

Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97.
Tel: 022 6144 1600;
Email: info@aakashpower.com;
www.aakashpower.com

(w.e.f. 3rd May 2021)

SOLAR WIRES / CABLES

Flexible Tinned Copper Conductor / Cross Linkable (E Beam) LSZH Insulation / Cross Linkable (E Beam) LSZH Sheathed Solar Cable as per EN 50618		Flexible Tinned Copper Conductor Single Core Multistrand, Cross Linked, Zero Halogen Low Smoke Sheathing, Heat Resistant upto 120° C and UV Resistant Solar Cables		Flexible Tinned Copper Conductor Multistrand XLPE / PVC Insulated & UV Stabilized PVC Sheathed Single Core Solar Cable	
Size in Sq. mm.	Rate Per 100 m	Size in Sq. mm.	Rate Per 100 m	Size in Sq. mm.	Rate Per 100 m
4	8000	4	7500	4	7300
6	11400	6	10900	6	10700
10	20700	10	20200	10	19800
16	32100	16	31400	16	29600
25	51500	25	50300	25	48000
35	77200	35	72500	35	65500
50	110300	50	103500	50	93500
70	154400	70			
95	209600	95			
120	264800	120			
150	330900	150			
185	408200	185			
240	529500	240			
300	661900	300			

Building Management System Cable (BMS)

Flexible Bare Copper Conductor, PVC Insulated, Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Rate/100m)

Cores	0.5 sq mm (16/.2)	0.75 sq mm (24/.2)	1.0 sq mm (32/.2)	1.5 sq mm (30/.25)	2.5 sq mm (50/.25)
2	6000	7250	8100	10400	16000
3	7500	9500	10800	14100	22200
4	9100	11800	13500	18000	28800
5	11000	14500	16800	21800	35300
6	12800	17000	19800	26300	42500
7	14300	18800	22500	30000	50000
8	16300	21800	25500	34000	56000
10	20000	26300	31300	42500	69400
12	23300	31300	36500	50000	82000
14	26500	36300	42500	57500	94900
16	30000	40300	47800	66300	111300
19	35000	47500	55500	77500	129100
24	44000	60000	70000	97500	161600

MANUFACTURERS AUTHORISED CHANNEL PARTNER / MARKETING REPRESENTATIVE:



**Cables
Motors
LV Switchgears
Cable Lugs & Glands
LED Lighting & Luminaires
Transformers**

Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97.
Tel: 022 6144 1600;
Email: info@akashpower.com;
www.akashpower.com

(w.e.f. 3rd May 2021)

INDUSTRIAL BRAIDED CABLES (Rate / 100 M)

Polycab Annealed Bare Cu Flexible Conductor PVC Insulated, Tinned Cu Braided (Screened) PVC Sheathed Flexible Unarmoured Cables 1100 Volts. (Rate per 100 Mtr)

Cores	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm	4 sq.mm.	6 sq mm	10 sq.mm	16 sq.mm	25 sq.mm	35 sq.mm
2	9200	10200	11800	14700	21400	36500	47100	84300	125900		
3	10800	12700	14700	19500	28700	45500	65400	104900	148500	255300	338800
4	12800	15800	19300	24100	36700	55300	78200	150800	203100	349600	453800
5	15900	20900	25500	29200	43700						
6	17200	22600	27100	33500	52900						
7	18900	24800	29000	39600	56000						
8	22000	28700	37000	46100	68900						
10	25600	34200	43000	56200	83600						
12	29000	39100	47900	61300	93300						
14	33800	47900	62000	82500	111600						
16	38400	61600	66000	90700	129700						
19	46100	71900	79200	108900	161500						
24	53400	77600	92300	135400	193100						

Note : 3% Extra Charges for Drum Packing

UNINYVIN CABLES

Multistranded Annealed Tinned Copper Conductor 105°C PVC Insulation with Nylon Braiding with Lacquer Coating Uninyvin Cables

Cable Size	Nom. Cnductor Area	Rate per Metre
22	0.347	21.50
20	0.556	27.75
18	0.966	41.00
16	1.170	48.75
14	2.050	74.50
12	3.220	109.00
10	5.330	154.00
8	8.760	239.00
6	13.300	354.00
4	21.500	559.00
2	33.300	857.00
1	40.700	1036.00
0	53.000	1346.00
00	68.300	1714.00
000	84.200	2124.00
0000	109.000	2730.00

MANUFACTURERS AUTHORISED CHANNEL PARTNER / MARKETING REPRESENTATIVE:



**Cables
Motors
LV Switchgears
Cable Lugs & Glands
LED Lighting & Luminaires
Transformers**

Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97.
Tel: 022 6144 1600;
Email: info@akashpower.com;
www.akashpower.com

(w.e.f. 3rd May 2021)

MULTICORE STEEL BRAIDED CABLES (Rate / 100 M)

"POLYCAB" Flex Bare Copper Conductor, PVC Insulated, Cores Laid Up Together PVC Inner Sheathed, GI Wire Braided (Flexible Armouring), Overall PVC Sheathed Steel Braided Cables.

Cores	0.5 Sq.mm.	0.75 Sq.mm.	1.0 Sq.mm.	1.5 Sq.mm.	2.5 Sq.mm.	4 sq.mm	6 sq.mm
2	9500	11300	12500	15700	22400	32100	43900
3	11300	13900	16100	20000	29400	43300	60900
4	13500	16600	19500	25600	37300	55400	78500
5	15700	19800	23500	30500	45200		
6	17900	22900	27100	35100	52900		
7	19300	25300	29900	38800	59400		
8	22000	28400	33600	44900	67800		
10	26300	34500	41300	54700	83800		
12	30300	39900	47500	63900	98300		
14	34500	45200	54000	73200	113100		
16	38300	50900	61200	82300	128300		
19	43700	58700	71300	96500	150200		
24	56200	74500	89100	120600	187900		
Cores	10.Sq.mm.	16.Sq.mm.	25.Sq.mm.	35.Sq.mm.	50.Sq.mm.	70.Sq.mm.	95.Sq.mm.
2	71200	105700	160200	217900	308700	423200	564300
3	99400	149400	228600	311800	442600	610200	816400
4	129500	195500	301200	410900	583600	805200	1078100

POLYCAB INDUSTRIAL SPEAKER WIRES

Speaker Wires (Oxygen Free) (Rate per 90 mtr)

Size	Price Per	Size	Price Per	Size	Price Per	Size	Price Per
23/36	2090	23/38	1635	0.5 Sq.mm	1985	1.5 Sq.mm	5180
40/36	3315	40/38	2540	0.75 Sq.mm	2885	2 Sq.mm	7995
70/36	5740	70/38	4010	1 Sq.mm	3570	2.5 Sq.mm	8240

Note : 3% Extra Charges for Drum Packing

MANUFACTURERS AUTHORISED CHANNEL PARTNER / MARKETING REPRESENTATIVE:



**Cables
Motors
LV Switchgears
Cable Lugs & Glands
LED Lighting & Luminaires
Transformers**

Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97.
Tel: 022 6144 1600;
Email: info@aakashpower.com;
www.aakashpower.com

(w.e.f. 3rd May 2021)

INDUSTRIAL WELDING CABLE

Polycab Flexible Copper Conductor 1100 Volts Welding Cable

Nominal Area of Conductor (Sq.mm)	Current Carrying Capacity	Conductor Construction Strands/ Dia in mm	TPR Insulation Rate / 100m (Rs)
16	120	509/0.2	37500
25	160	796/0.2	56000
35	230	1115/0.2	78800
50	400	703/0.3	112500
70	600	999/0.3	156800
95	700	1346/0.3	211800
120	1100	1699/0.3	262000

FESTOON CABLES

(Price in Rs/Mtr)

Cores	0.5	0.75	1	1.5	2.5	4			
3	62	78	96	126	207	316			
4	81	104	126	173	272	424			
5	113	148	188	240	380	570			
6	135	180	223	285	458	688			
7	155	205	258	330	533	798			
8	180	233	293	380	613	915			
9	208	275	343	435	705	1045			
10	230	303	378	483	780	1165			
12	270	360	450	573	930	1390			
14	328	423	528	683	1093	1633			
16	370	485	610	775	1255	1870			
18	408	535	683	870	1390	2078			
24	555	728	925	1050	1875	2813			

INDUSTRIAL TELEPHONE (SWITCHBOARD) CABLES

"POLYCAB" High Conductivity Solid Annealed Bare Copper industrial Telephone (Switchboard) Cables with High Density Polyethylene Insulation, Paired, Polyester and Sheathed with High Oxygen Index, Fire Retardant, PVC Compound, Grey Outer Sheath generally conforming ITD Specification

No. of Pairs & Size	Rate / 100m (Rs.)		Rate / 90m (Rs.)		Master Packing
	0.4 mm	0.5 mm	0.4 mm	0.5 mm	
1 Pair	835	1155	750	1040	20
2 Pair	1310	2040	1230	1835	20
3 Pair	1895	2930	1705	2635	16
4 Pair	2425	3850	2180	3465	12
5 Pair	3125	4580	2810	4120	8
10 Pair	6385	9350	5745	8415	1
20 Pair	11885	18480	10695	16630	1
50 Pair		46200	0	0	1
100 Pair		97000	0	0	1

MANUFACTURERS AUTHORISED CHANNEL PARTNER / MARKETING REPRESENTATIVE:



Cables
Motors
LV Switchgears
Cable Lugs & Glands
LED Lighting & Luminaires
Transformers

Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97.
Tel: 022 6144 1600;
Email: info@aaakashpower.com;
www.aaakashpower.com