

(WEF 12th Feb 2020)

Building Management System Cable (BMS)

Flexible Bare Copper Conductor, PVC Insulated, Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Rate/100m)

Cores	0.5 sq mm (16/.2)	0.75 sq mm (24/.2)	1.0 sq mm (32/.2)	1.5 sq mm (30/.25)	2.5 sq mm (50/.25)
2	4400	5400	6100	8000	12000
3	5400	6900	8100	10500	16300
4	6500	8500	9900	15000	23500
5	7800	11900	12000	16700	25500
6	8700	13400	14400	19200	30300
7	9500	13700	15800	21500	34300
8	11100	15200	17800	24300	38800
10	12900	17400	22000	30100	48900
12	15200	20400	26000	35900	57100
14	17600	23700	29800	40600	66200
16	20200	26900	33800	47000	75500
19	23000	31000	39000	54500	86800
24	27500	38000	49100	68800	112400

Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97.

Tel: 022 6144 1600; Email: info@aakashpower.com; www.aakashpower.com

Rev.001 - 12.02.2020