



LDC Pricelist



WEF 12th February 2020

Polycab PVC Insulated, FRLS Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal Area of Conductor (sq mm)	Number/Nom. Dia of Conductor (No./dia mm)	Current Carryig Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	6550	7400	8800	10500
0.75	24/.2	8	9000	10200	12500	14700
1	32/.2	13	11300	12700	15800	18700
1.5	30/.25	17	15300	17500	21400	25200
2.5	50/.25	24	24400	27800	34500	41100
4	56/.3	30	38300	43400	53800	64000
6	84/0.3	37	61200			
Nominal Area of Conductor (sq mm)	Number/Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	12200	13700	16000	21300
0.75	24/.2	8	16800	19400	22700	30000
1	32/.2	13	21400	24500	29100	38000
1.5	30/.25	17	29400	33400	39600	51300
2.5	50/.25	24	47600	54400	63600	84200

**Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-('E), Mum- 97. Tel: 022 6144 1600; Email:
info@akashpower.com; www.akashpower.com**

Rev.001 - 12.02.2020