

(WEF 12th Feb 2020)

SOLAR WIRES / CABLES

| Flexible Tinned Copper Conductor / Cross Linkable (E Beam) LSZH Insulation / Cross Linkable (E Beam) LSZH Sheathed Solar Cable as per EN 50618 | | Flexible Tinned Copper Conductor Single Core Multistrand, Cross Linked, Zero Halogen Low Smoke Sheathing, Heat Resistant upto 120° C and UV Resistant Solar Cables | | Flexible Tinned Copper Conductor Multistrand XLPE / PVC Insulated & UV Stabalized PVC Sheathed Single Core Solar Cable | |
|--|----------------|--|----------------|--|----------------|
| Size in Sq. mm. | Rate Per 100 m | Size in Sq. mm. | Rate Per 100 m | Size in Sq. mm. | Rate Per 100 m |
| 4 | 5725 | 4 | 5325 | 4 | 4850 |
| 6 | 8050 | 6 | 7750 | 6 | 7175 |
| 10 | 16000 | 10 | 15300 | 10 | 13000 |
| 16 | 23200 | 16 | 22300 | 16 | 20100 |
| 25 | 38400 | 25 | 36900 | | |
| 35 | 53800 | 35 | 51500 | | |
| 50 | 76800 | 50 | 73600 | | |
| 70 | 107600 | 70 | 103100 | | |
| 95 | 146100 | 95 | 139900 | | |
| 120 | 184500 | 120 | 176700 | | |
| 150 | 230600 | 150 | 221000 | | |
| 185 | 284400 | 185 | 272500 | | |
| 240 | 369000 | 240 | 353500 | | |
| 300 | 461200 | 300 | 441800 | | |
| | | | | | |

Add: 501-505, A-Wing, Express Zone, W.E.H, Malad-(E), Mum- 97.

Tel: 022 6144 1600; Email: info@akashpower.com; www.akashpower.com

Rev.001 - 12.02.2020